



OptiNID® 500 Optical Demarcation Closure

The OptiNID (OPN) 500 is an optical demarcation closure designed for use in either indoor or outdoor environments. Small form factor for FTTH demarcation applications, the closure is capable of housing up to six bulkhead adapters in one 118 LGX® compatible adapter plate, and is equipped with an integrated splice tray, which holds up to six single fusion splices. The OPN-500 can be either wall or pole-mounted.

Features

- Weather-resistant thermoplastic alloy
- Self-latching, hinged cover design allows easy access without loose parts
- Capacity for one 118 LGX compatible adapter plate
- Provider override for customer lock
- 3/4" NPT conduit fitting, compression cable fittings or grommets entry ports



Specifications

PARAMETER	VALUES
Dielectric Strength	Minimum 2500 Vrms for 1 minute
High Temperature Storage/Mold Stress °F (°C)	14 days at 159 (70.55)
Temperature Cycling with Humidity °F (°C)	150 day cycling from 40-140 (4.44-60) with 95% RH
Impact Test °F (°C)	-40 (-40), 5 ft/lbs on all external surfaces
Drop Test °F (°C)	-40 (-40), 5 ft onto concrete surface four times
Rain	24 hours at 10 psi
UV Resistance (Days Exposed)	60 per ASTM-G26-84
Salt Fog (Days Exposed)	60 per ASTM-BLL7-90
Flammability	UL94-5V
Chemical Resistance 30 Days at 100°F and 95% RH	Resists chipping and/or cracking when subject to house paint, wasp spray, sulfuric acid, kerosene and sodium hydroxide
Material	UL® listed flame retardant thermoplastic alloy
Dimensions (H x W x D) in. (cm)	6.3 x 7.8 x 2.0 (15.7 x 19.7 x 5.0)
Cable Entrance in. (cm) diameter - Input	1 x 3/4" NPT (1.130"), 2 x 1/2" NPT (0.875")
Covers	Standard, molded-in snap finger and "F" termination



Ordering Information

DESCRIPTION	AFL NO.
BASE PRODUCT ^{1,2}	
OptiNID OPN-500, No Adapters	DM001021
OptiNID OPN-500, 1 x SC/UPC Adapter	DM000550
OptiNID OPN-500, 1 x SC/APC Adapter	DM000766
OptiNID OPN-500, 6 x SC/UPC Adapters	DM000871
OptiNID OPN-500, 6 x SC/UPC Adapters, 6 x 1 m 900 µm Pigtailed	DM001109
ACCESSORIES ³	
Heyco M3234 Compression Fitting, 18 mm to 11 mm Grip (includes 4) – Left Port Only	DM001171
Kit, Six-Position Splice Chip, (includes 10)	DM000870

Notes:

1. All standard OPN-500 configurations come equipped with a 3/4" NPT fitting, rubber grommet and Heyco 3231 compression fitting, along with a splice chip for six single fusion splices.
2. Contact AFL customer service for additional configurations.
3. See OptiNID Accessory Page for additional kits.

LGX is a registered trademark of Furukawa Electric North America, Inc.